



News Release | www.linear.com

High Accuracy Temperature & Dual Voltage Monitor Provides Flexible Alert Outputs

MILPITAS, CA – May 7, 2012 – Linear Technology Corporation introduces the [LTC2995](#) high accuracy temperature sensor and dual supply monitor for low voltage systems. The LTC2995 measures a remote diode's temperature with $\pm 1^{\circ}\text{C}$ accuracy and its own die temperature with $\pm 2^{\circ}\text{C}$ accuracy, while rejecting errors due to noise and series resistance. Two voltage rails, one of which is required to be between 2.25V and 5.5V to power the device, are monitored with $\pm 1.5\%$ accuracy, minimizing the required system supply margins. The LTC2995 provides a voltage-proportional-to-absolute-temperature (V_{PTAT}) output, as well as individual undertemperature, overtemperature, undervoltage and overvoltage alert outputs defined by user-adjustable thresholds. No code is required to configure the device. The LTC2995 combines the functionality of a temperature monitor and dual voltage monitor in a space-saving, micropower solution.

The LTC2995's accuracy, configurability and code-free operation caters to a wide variety of applications, including system thermal control, energy harvesting, desktop and notebook computers, network servers and environmental monitoring. Users can choose to measure local temperature, remote temperature, or both in alternation, while two temperature output pins can be configured to be any combination of undertemperature and/or overtemperature alerts. Temperature conversions are updated every 3.5ms to provide systems with sufficient time to react to alerts. A 1.8V voltage reference output is also available to share with an external ADC or for generating temperature threshold voltages. When monitoring voltages, an input glitch filter reduces false resets due to noise, while both supplies share one overvoltage and undervoltage pin. All thresholds are easily adjusted with resistive dividers, and the reset delay time for all alert outputs can be adjusted with just a single capacitor. The LTC2995 draws only 220 μA of supply current over the full operating temperature range.

The LTC2995 is offered in commercial, industrial and automotive versions, supporting operating temperature ranges from 0°C to 70°C , -40°C to 85°C and -40°C to 125°C ,

respectively. The LTC2995 is available today in a RoHS compliant, 20-pin, 3mm x 3mm QFN package. Pricing starts at \$2.45 each in 1,000 piece quantities. For more information, visit www.linear.com/product/LTC2995


Photo Caption: Dual OV/UV Supply & Single OT/UT Remote Temperature Monitor

Summary of Features: LTC2995

- Monitors Temperature & Two Voltages
- Voltage Output Proportional to Temperature
- Adjustable Thresholds for Temperature & Voltage
- $\pm 1^{\circ}\text{C}$ Remote Temperature Accuracy
- $\pm 2^{\circ}\text{C}$ Internal Temperature Accuracy
- $\pm 1.5\%$ Voltage Threshold Accuracy
- 3.5ms V_{PTAT} Update Time
- 2.25V to 5.5V Supply Voltage
- Adjustable Reset Timeout
- 1.8V Reference Voltage Output
- Open Drain Alert Outputs
- 20-Pin 3mm x 3mm QFN Package

About Linear Technology

Linear Technology Corporation, a member of the S&P 500, has been designing, manufacturing and marketing a broad line of high performance analog integrated circuits for major companies worldwide for three decades. The Company's products provide an essential bridge between our analog world and the digital electronics in communications, networking, industrial, automotive, computer, medical, instrumentation, consumer, and military and aerospace systems. Linear Technology produces power management, data conversion, signal conditioning, RF and interface ICs, $\mu\text{Module}^{\text{®}}$ subsystems, and wireless sensor network products. For more information, visit www.linear.com

LT, LTC, LTM, μModule and  are registered trademarks of Linear Technology Corp. All other trademarks are the property of their respective owners.

Press Contacts:

North America / Worldwide

John Hamburger, Director Marketing
Communications
jhamburger@linear.com
Tel: 408-432-1900 ext 2419

Doug Dickinson, Media Relations Manager
ddickinson@linear.com
Tel: 408-432-1900 ext 2233

UK & Nordic

Alan Timmins
alan@ezwire.com
Tel: +44-1-252-629937