



News Release | www.linear.com

65V, 500mA Synchronous Buck Converter Delivers 90% Efficiency & Requires Only 12 μ A Quiescent Current

MILPITAS, CA – May 29, 2012 – Linear Technology announces the [LTC3630](#), a 65V input-capable synchronous buck converter, which delivers up to 500mA of continuous output current from a 3mm x 5mm DFN (or MSOP16-E) package. Its internal synchronous rectification topology delivers efficiencies as high as 90% and its Burst Mode[®] operation requires only 12 μ A of quiescent current (at no load), maximizing battery run time. The LTC3630 operates from an input voltage range of 4V to 65V, making it suitable for a wide range of applications, including automotive, industrial, medical and avionics.

The LTC3630's internal synchronous rectification and its programmable peak current limit design optimize efficiency while minimizing output ripple and external component size. Furthermore, output current can be programmed between 50mA and 500mA with a single resistor. The LTC3630's output voltage can be adjusted with an external resistor divider to voltages from 0.8V to V_{IN} , or it can be easily programmed to deliver a fixed 1.8V, 3.3V or 5V output with 1% accuracy. The combination of its 3mm x 5mm DFN package (or thermally enhanced MSOP-16) and only three tiny externals offers a highly compact solution footprint for a wide array of general purpose applications.

The LTC3630 utilizes internal high side and low side power MOSFETs to ensure high efficiency in a very compact footprint. Additionally, the LTC3630 offers a precise run threshold and soft-start feature to ensure that system start-up is well controlled in any environment.

Furthermore, a feedback comparator output enables multiple LTC3630s to be paralleled for higher current applications. Due to the inherent stability of the converter, no external compensation is required, thereby minimizing the solution footprint.

Pricing for the LTC3630EDHC and the LTC3630EMSE starts at \$3.20 each. Industrial grade versions, the LTC3630IDHC and LTC3630IMSE, are tested and guaranteed to operate over a -40°C to 125°C operating junction temperature range and are priced at \$3.55 each.

Automotive grade versions, the LTC3630HDHC and LTC3630HMSE, are tested and guaranteed to operate from -40°C to 150°C operating junction temperature and are priced at \$3.80 each.

Military Plastic grade versions, the LTC3630MPDHC and LTC3630MPMSE, are tested and guaranteed to operate over a -55°C to 150°C operating junction temperature range and are priced at \$10.72 each. All pricing is for 1,000-piece quantities and all versions are available from stock.

For more information, visit www.linear.com/product/LTC3630


Photo Caption: 65V, 500mA Synchronous Buck Converter Delivers 90% Efficiency

Summary of Features: LTC3630

- Wide Operating Input Voltage Range: 4V to 65V
- Synchronous Operation for Highest Efficiency
- Internal High Side & Low Side Power MOSFETs
- No Compensation Required
- Adjustable 50mA to 500mA Maximum Output Current
- Low Dropout Operation: 100% Duty Cycle
- Low Quiescent Current: 12 μ A
- Wide Output Range: 0.8V to V_{IN}
- 0.8V \pm 1% Feedback Voltage Reference
- Precise RUN Pin Threshold
- Internal & External Soft-Start
- Programmable 1.8V, 3.3V, 5V or Adjustable Output
- Few External Components Required
- Low Profile (0.75mm) 3mm \times 5mm DFN & Thermally Enhanced MSE16 Packages

About Linear Technology

Linear Technology Corporation, a member of the S&P 500, has been designing, manufacturing and marketing a broad line of high performance analog integrated circuits for major companies worldwide for three decades. The Company's products provide an essential bridge between our analog world and the digital electronics in communications, networking, industrial, automotive, computer, medical, instrumentation, consumer, and military and aerospace systems. Linear Technology produces power management, data conversion, signal conditioning, RF and interface ICs, µModule® subsystems and wireless sensor network products. For more information, visit www.linear.com

LT, LTC, LTM, µModule, Burst Mode and  are registered trademarks of Linear Technology Corp. All other trademarks are the property of their respective owners.

Press Contacts:

North America / Worldwide

John Hamburger, Director Marketing
Communications
jhamburger@linear.com
Tel: 408-432-1900 ext 2419

Doug Dickinson, Media Relations Manager
ddickinson@linear.com
Tel: 408-432-1900 ext 2233

UK & Nordic

Alan Timmins
alan@ezwire.com
Tel: +44-1-252-629937